


**PATENT**  
**5259-03700**

**"EXPRESS MAIL" MAILING LABEL**

NUMBER: EL530672587US

DATE OF DEPOSIT January 6, 2000

I hereby certify that this paper is being deposited with the United States Postal Service "EXPRESS MAIL POST OFFICE TO ADDRESSEE" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to: The Assistant Commissioner for Patents, Washington, D.C. 20231.

  
Debra J. Vix

**SYSTEM AND METHOD  
FOR STABILIZING THE HUMAN SPINE  
WITH A BONE PLATE**

By:

Jim Freid

Michael E. Landry

and

Erik J. Wagner

Atty. Dkt. No.: 5259-03700

Eric B. Meyertons  
Conley, Rose & Tayon, P.C.  
P.O. Box 398  
Austin, TX 78767-0398  
Ph: (512) 476-1400

10015206.1001

21

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

5 The present invention generally relates to spinal fixation systems and the like. The present invention also generally relates to a spinal plate system that includes a mechanism for fixably attaching heads of fasteners to a spinal plate.

### 2. Description of the Related Art

10 The use of spinal fixation plates for correction of spinal deformities and for fusion of vertebrae is well known. Typically, a rigid plate is positioned to span bones or bone segments that need to be immobilized with respect to one another. Bone screws may be used to fasten the plate to the bones. Spinal plating systems are commonly used to correct problems in the lumbar and cervical portions of the spine, and are often installed posterior or anterior to the spine.

15 Spinal plate fixation to the cervical portion of the spine may be risky because complications during surgery may cause injury to vital organs, such as the brain stem or the spinal cord. When attaching a fixation plate to a bone, bone screws are placed either bi-cortically (i.e., entirely through the vertebrae such that a portion of the fastener extends into the spinal cord region) or uni-cortically (i.e., the fastener extends into but not through the vertebrae). Uni-cortical positioning of bone screws has grown in popularity because it is generally safer to use. Bi-cortical fasteners are intended to breach the distal cortex for maximum anchorage into the bone; however, this placement of the fasteners may place distal soft tissue structures at risk. Fastener placement is particularly important in 20 anterior cervical plate procedures because of the presence of the spinal cord opposite the distal cortex. Unfortunately, uni-cortical fasteners may move from their desired positions because of the soft texture of the bone marrow. In fact, the portion of the bone surrounding such fasteners may fail to maintain the fasteners in their proper positions. 25 The result is backout of the fastener.

Backout of the fastener is particularly problematic when two fasteners are implanted perpendicular to the plate. When the fasteners are placed in such a manner, backout may occur as a result of bone failure over a region that is the size of the outer diameter of the fastener threads. To overcome this problem, two fasteners may be angled in converging or diverging directions with respect to each other within the bone. The amount of bone that is required to fail before backout may occur is increased by this configuration as compared to fasteners that are implanted in parallel. Although positioning convergent or divergent fasteners in a bone reduces the risk of backout, backout may still occur.

Backout may damage internal tissue structures and cause complications if the dislocated fastener penetrates the tissue structures. For example, if backout occurs, the fastener might breach the esophageal wall of the patient. Such a breach may permit bacterial contamination of surrounding tissues, including the critical nerves in and around the spinal cord. Such a breach could be fatal.

In an attempt to reduce the risk of damage to internal tissue structures, some cervical fastener plate systems have uni-cortical fasteners that attach both to the bone and to the plate. If a fastener does backout, the fastener remains connected to the plate so that it does not contact internal tissue structures. U.S. Patent No. 5,364,399 to Lowery *et al.* describes one such system and is incorporated by reference as if fully set forth herein.

The Lowery *et al.* plating system includes a locking fastener at each end of the plate. The locking fastener engages the head of the bone screw to trap the fastener within a recess of the plate. Since the locking fastener is positioned over portions of the bone screws, the locking fastener may extend above the upper surface of the plate. Thus, the locking fastener may come into contact with internal tissue structures, such as the esophagus.

Another plating system that includes a fastener-to-plate locking mechanism is the Aline™ Anterior Cervical Plating System sold by Smith & Nephew Richards Inc. in Memphis, Tennessee. A description of this system can be found in the Aline™ Anterior Cervical Plating System Surgical Technique Manual by Foley, K.T. et al., available from Smith & Nephew Richards Inc., 9/96, pp. 1-16 and is incorporated by reference as if fully

set forth herein. The bone screws of this system have openings within each bone screw head for receiving a lock fastener coaxially therein. Each bone screw may be inserted into a bone such that the head of the fastener is positioned within a hole of a plate placed adjacent to the bone. The head of each bone screw is slotted so that portions of the head are deflected toward the plate during insertion of the lock fastener within the opening of the bone screw. Positioning and inserting a lock fastener within the opening can be difficult due to the small size of the lock fastener. The surgeon may be unable to hold onto the lock fastener without dropping it. If a lock fastener falls into the surgical wound, it may be difficult to retrieve. In some instances, the lock fastener may be unretrievable.

### SUMMARY OF THE INVENTION

An implant system may be used to immobilize a portion of a human spine. The implant system may include a plate comprising end holes, midline holes, fasteners, and expandable/contractible rings. The fasteners and rings may include mechanisms for anchoring or locking the fastener heads within the rings to inhibit backout of the fastener.

The end holes extend from an upper surface to a lower surface of the plate. The end holes may be disposed in pairs at opposite ends of the plate. Each end hole receives at least a portion of a head of a fastener. Herein, "fastener" means any elongated member, threaded or non-threaded, which is securable within a bone. Fasteners include, but are not limited to screws, nails, rivets, trocars, pins, and barbs. The fastener may be a bone screw. A fastener may have a fastener head. The fastener head typically includes an opening adapted to mate with a tool. The tool allows the insertion of the fastener into a bone. Each end hole may also be spherically contoured to permit the fastener to be "obliquely angulated" relative to the plate. Herein, "obliquely angulated" means that the fastener may be positioned throughout a wide range of angles relative to an axis that is perpendicular to the plate. Obliquely angulating a fastener into a bone may reduce the risk of backout of the fastener.

The expandable/contractible rings may be sized so that a ring seats within an end hole between the plate and the fastener. The inner surface of each ring may be shaped to

mate with a fastener head while the outer surface may be shaped to mate with the inside surface of an end hole. The outer surface of each fastener head may be tapered so that an upper portion of the head is larger than a lower portion of the head. The inner surface of the ring may have a taper that generally corresponds to the taper of the fastener head.

5 Each ring may also have a gap that extends vertically through the ring to make the ring more readily expandable and contractible. During insertion of the fastener head into the ring, the fastener head exerts force against the ring to expand the ring against the inner surface of the hole. Expanding the ring against the inner surface of the hole may securely fix the fastener to the plate.

10 The fastener head and the ring may include a locking mechanism to attach the fastener head to the plate. The locking mechanism may inhibit backout of the fastener head from the ring if the fastener loosens in the bone. The locking mechanism may also inhibit the fastener head from contacting adjacent tissue structures since the locking mechanism attaches the fastener head to the plate. In some embodiments, there is  
15 tolerance for some freedom of movement in an axial direction between a locking mechanism and a fastener head. The availability of some axial movement may allow the fastener to back out or loosen slightly from the bone during a normal period of adjustment after implantation of a spinal fixation system.

20 Midline holes may be formed through the plate at various locations along a midline axis extending across the plate. The surface of the plate that surrounds each midline hole may be tapered. Further, the heads of fasteners that may be positioned within the plates may have tapered outer surfaces that generally correspond to the tapered surface of the plate. Thus, when such a fastener head is inserted into a midline hole, the shape of the plate causes the fastener to become fixably attached to the plate in a position  
25 that is substantially perpendicular to the plate. Midline holes may be used to attach a bone graft to the bore plate. Oblique angulation of fasteners positioned within the midline holes may not be required.

The bone plate may have one or more spikes located on the surface of the plate that faces the spinal column. Spikes may be disposed in pairs at opposite ends of the

plate proximate the end holes. The spikes may be tapped into the bone to help inhibit the bone plate from slipping during surgical implantation.

Prior to surgical implantation of the spinal plate system, the expandable/contractible rings may be placed within the end holes of the plate. The plate may then be positioned adjacent to a portion of the spine that requires spinal fixation. Holes may be drilled and/or tapped at desired angles into portions of the bone underlying the end holes of a plate. Fasteners may be inserted through the end holes into the holes in the bone. The heads of the fasteners may be positioned within the end holes such that the rings surround at least a portion of the heads. The rings may lock the fasteners in place without occupying regions outside of the end holes. Further, since the rings are pre-positioned within the end holes, surgeons do not have to worry that they may drop the rings during insertion of the rings into the end holes of the plate.

In one embodiment, a locking mechanism secures a fastener head to a ring. A locking mechanism may have a top and one or more flexible arms that angle downwards and outwards from the top. The ends of the arms have prongs that are substantially parallel to the top of the locking mechanism. A locking mechanism in a compressed configuration, fits into an opening formed in the head of a fastener. The prongs of the locking mechanism fit within holes located near the bottom of the opening. The holes extend from the outer surface of the head to the opening. When the prongs are positioned in the holes, the prongs extend through the holes so that the locking mechanism is in an extended configuration. The prongs that extend out of the head of the fastener fit within a groove on the inner surface of the ring to enhance the connection between the fastener and the ring.

The locking mechanism may be inserted in the fastener head prior to the surgical procedure to avoid the risk of dropping the locking mechanism during the surgical procedure. An insertion and extraction tool retracts the prongs on the locking mechanism into the head during insertion or extraction of a fastener. The tool may include a handle, a shaft, and a hollow driver head shaped to match a drive section of the opening on the fastener head. Inserting the driver head into the opening slides the head over the locking

mechanism and compresses the shafts of the locking mechanism. Compressing the shafts of the locking mechanism retracts the prongs into the fastener head. To insert a fastener into a bone, the user inserts the fastener into the bone until the head is fully inserted in the ring. Removing the driver head from the opening causes the shafts of the locking mechanism to expand outwards so that the prongs extend out of the holes into the fastener head.

To remove a fastener that has a locking mechanism, the user inserts the driver head of the insertion and extraction tool into the opening of the fastener head. The driver head compresses the shafts of the locking mechanism and causes the prongs to retract within the fastener head. The user may then remove the fastener from the bone.

In another embodiment, a tapered fastener head locks into a ring by one or more fingers on the ring that snap into grooves on the fastener head. L-shaped slots cut into the top of the ring may define the fingers. The fingers have springlike action so that the fingers snap into the grooves on the fastener head when a fastener head is inserted into the ring. As the fastener head passes into the ring, the tapered outer surface of the head expands the ring against the inner surface of the plate. When the groove on the fastener head reaches the fingers, the fingers snap into the groove, fixing the fastener in the ring and helping to inhibit backout.

In another embodiment, a fastener head locks to a ring by one or more ridges on the ring that snap into grooves on the fastener head. Notches cut into the top of the ring may form paddles. A ridge may extend along an inside surface of each paddle proximate the top of the ring. The paddles have a springlike action so that the ridges snap into the grooves on the fastener head during insertion of the fastener head into the ring. The ridges of the ring residing within a groove of the fastener head may fix the fastener in the ring and help inhibit backout of the fastener.

An extraction tool module fits over an insertion tool and allows the retraction of the ring ridges from the fastener head. The insertion tool includes a handle, a shaft, and a driver head shaped to match the opening on the fastener head. The extraction module slides over the shaft of the insertion tool. The extraction module may include a handle

and an extraction head. The extraction head may include a tip that slides over the fastener head and contacts the ends of the paddles. The outer surface of the tip tapers. As the extraction module is pushed down, the tapered surface of the tip forces the paddles outwards and disengages the ridges on the paddles from the grooves on the fastener head.

5 Disengaging the ridges on the paddles from the grooves on the fastener head allows the fastener to be backed out of the bone.

Using a locking mechanism between the fastener head and the ring may result in a strong connection between the fastener and the plate. Even if the shank of a fastener loosens within the bone, the fastener head will tend to remain within the hole of the plate so as not to protrude from the plate into surrounding body tissue. Allowing some axial freedom of movement for the fastener head in the ring may allow the fastener to back out slightly during an adjustment period after installation of the spinal fixation system.

#### BRIEF DESCRIPTION OF THE DRAWINGS

15 *dc37* Further advantages of the present invention will become apparent to those skilled in the art with the benefit of the following detailed description of embodiments and upon reference to the accompanying drawings in which:

Figure 1 is a top view of an embodiment of a spinal plating system that may be used for fixation of the human spine.

20 Figure 2 is a partial cross-sectional view of the spinal plating system taken substantially along line 2-2 of Figure 1. The fastener is not shown in section.

Figure 3 is a partial cross-sectional view of the spinal plating system taken substantially along line 3-3 of Figure 1, wherein the fasteners are in a converging orientation within end holes of a plate. The fasteners are not shown in section.

25 Figure 4 is a partial cross-sectional view of the spinal plating system taken substantially along line 4-4 of Figure 1, wherein the fasteners are in a diverging orientation within end holes of a plate 5, the fasteners are not shown in section.



Figure 5 depicts an embodiment of a fastener with grooves and holes to engage a locking mechanism.

Figure 6 is a partial front view of a fastener with holes in the fastener head.

Figure 7 is a top view of a fastener head having grooves for engaging a locking mechanism.

Figure 8 is a top view of an embodiment of a fastener head with a hexagonal opening and holes to engage a locking mechanism.

Figure 9 is a perspective view of a locking mechanism.

Figure 10 is a perspective view of a ring that may be used with a fastener and a locking mechanism.

Figure 11 is a partial sectional view of an insertion/extraction tool for fasteners with locking mechanisms.

Figure 12a is a bottom view of a driver head of the insertion/extraction tool shown in Figure 11. The tool may be used with the fastener head shown in Figure 7.

Figure 12b is a bottom view of the driver head of the insertion and removal tool shown in Figure 11 which may be used with the fastener head shown in Figure 8.

Figure 13 is a sectional view of a fastener head with an insertion/extraction tool and compressed locking mechanism during an insertion process.

Figure 14 is a sectional view of a fastener head and locking mechanism inserted into a ring.

Figure 15 is a perspective view of an embodiment of a fastener.

Figure 16 is a front view of an embodiment of a fastener head.

Figure 17 is a perspective view of an embodiment of a fastener.

Figure 18 is a front view of an embodiment of a fastener head with a groove.

Figure 19 is a perspective view of an embodiment of a ring.

Figure 20 is a perspective view of an embodiment of a ring.

Figure 21 is a perspective view of an embodiment of a ring.

Figure 22 is front view of an insertion/extraction tool which may be used with the ring of Figure 21.

5 Figure 23a is a partial cross sectional view of a fastener during insertion in the ring of Figure 21. The shaft of the insertion/extraction tool is not shown in cross section.

Figure 23b is a partial cross sectional view of a fastener after insertion in the ring of Figure 21. The shaft of the insertion/extraction tool is not shown in cross section; and

10 Figure 23c is a partial cross sectional view of a fastener during removal from the ring of Figure 21. The shaft of the insertion/extraction tool is not shown in cross section.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but to the contrary, the intention is to cover all modifications, equivalents and  
- alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

## 20 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

dc47 Referring to the drawings, and particularly to Figure 1, a spinal plating system is designated generally as 20. The spinal plating system 20 may be used to correct problems in the lumbar and cervical portions of the spine. For example, the plating system 20 may be implanted into the occiput bone that is located at the base of the skull.

25 The plating system 20 may also be installed anterior to the spine. The spinal plating system 20 includes plate 22 that is placed adjacent to a portion of the spine and spans at least two vertebrae. Plate 22 may include four end holes 24, located at corners of the plate. End holes 24 pass vertically through plate 22 such that the holes extend from an

upper surface 26 to a lower surface 28 of the plate as depicted in Figure 2. End holes 24 are configured to receive rings 30. Fasteners 32 fit within the rings 30. Herein, "fastener" means any elongated member, threaded or non-threaded, which is securable within a bone. Fasteners include, but are not limited to screws, nails, rivets, trocars, pins, and barbs. The fastener may be a bone screw. Rings 30 fixedly attach fastener heads 34 of fasteners 32 to plate 22. Gap 36 may exist in each of the rings 30. A gap 36 allows for expansion and contraction of a ring 30. Ring contraction allows a ring 30 to be easily inserted into an end hole 24 of the plate 22.

The spinal plating system 20 may also include one or more central holes 38 that extend vertically through plate 22. One of the central holes 38 may be located at about the mid-point of the plate 22. Head 40 of fastener 42 is positioned within one of the central holes 38. Multiple central holes 38 provide a surgeon with options as to the most desirable location for placement of a fastener 42. Fastener 42 may be used to connect plate 22 to a bone graft (not shown).

Figure 2 shows a fastener 42 within one of the central holes 38 of plate 22. Fastener 42 may include head 40 and shank 44. The shank 44 extends from the base of head 40. In one embodiment, the inner surface of a central hole 38 tapers so that the hole is larger at upper plate surface 26 than at the lower plate surface 28. The outer surface of the fastener head 40 has a taper that generally corresponds to the taper of the central hole 38. During implantation of a fastener 42 into a bone graft, the shank 44 of the fastener 42 is inserted into a hole that has been formed in the bone graft under hole 38. Because the lower portion of hole 38 is smaller than the upper portion of the fastener head 40, fastener 42 may become locked into place within the central hole 38 once the fastener has been inserted to a desired depth within the bone graft. The bone plate 22 may have spikes 45 extending from the lower plate surface 28.

As shown in Figure 2, the plate 22 may have a curvature. The curvature may enhance fixation of the plate 22 to a bone. The bone plate 22 may have one or more spikes 45 located on the surface of the plate that faces the bone. The spikes 45 may be disposed in pairs at opposite ends of the plate proximate the end holes 24. The spikes 45

may be tapped into the bone to help inhibit the bone plate 22 from slipping during surgical implantation.

dc37 Figure 3 depicts a cross-sectional view of an embodiment of a final plating system 10 wherein a pair of fasteners 32 are in a converging configuration. Figure 4 depicts a cross-sectional view of an embodiment of a spinal plating system wherein a pair of fasteners 32 are in a diverging configuration. Ring 30 fits into a hole 24 between plate 22 and fastener head 34. Inner surfaces 46 of holes 24 may have arcuate or spherical contours. Outside surfaces 48 of rings 30 may have arcuate or spherical contours that substantially correspond to the contours of the inner surfaces 46 of the holes 24. Having a contoured ring outer surface 48 that substantially corresponds to the contour of the inner hole surface 46 allows a ring 30 positioned in a hole 24 to be capable of polyaxial rotation within the end hole 24.

The combination of ring 30 within end hole 24 functions like a ball and socket since the ring may be swiveled or polyaxially rotated within the end hole. The ability of the ring 30 to rotate polyaxially within the end hole 24 allows a fastener 32 to be positioned through the plate 22 at various angles with respect to an axis that is perpendicular to the plate. Figure 3 and 4 show angle A for particular fastener configurations. The angle A is defined between the longitudinal axis 50 of the fastener 32 and imaginary axis 52 that is perpendicular to the plate 22. The angle A may range from 0 to about 45 degrees, preferably from about 0 to about 30 degrees, and more preferably from 0 to about 0 and 15 degrees.

Fasteners 32 may also be set in positions such that the fasteners are non-planar with respect to a latitudinal plane extending through plate 22. For example, one fastener 32 may be positioned out of the page and another fastener 32 may be positioned into the page, as depicted in Figures 3 and 4. Fasteners 32 set in diverging or converging directions in the end holes 24 may reduce the possibility of backout. Further, the use of rings 30 to fixedly attach fasteners 32 to plate 22 may inhibit damage to tissue structures by any fasteners that do loosen within a bone, since such fasteners would remain attached to the plate 22. Fasteners 32 may be placed in uni-cortical positions within a bone since

the problem of fastener backout is reduced by having obliquely angulated fasteners in converging or diverging configurations.

Ring 30 may at least partially surrounds head 34 of fastener 32 positioned within end hole 24. A shank 54 of fastener 32 may include threading 56 to allow the fastener to be inserted into a bone when fastener 32 is rotated. As depicted in Figure 1, fastener head 34 may include a cavity 58 that extends from the top of the head to an inner portion of the head. Cavity 58 may be shaped to receive an end of a tool that inserts or removes the fastener 32 from a bone. The tool end may be in the form of a hex wrench, a star wrench or a screwdriver blade.

Inner surface 60 of ring 30 and outer surface 62 of head 34 may have mating tapered surfaces, as depicted in Figure 3 and Figure 4. In one embodiment, the bottom portion of head 34 may be smaller than the upper portion of an unstressed ring 30, while the upper portion of the head may be larger than the upper portion of the ring. As fastener 32 is inserted into a bone, head 34 applies a radial force to ring 30 which causes the ring to expand within the end hole 24. Expanding the ring 30 increases the size of gap 36 and may cause the outside surface 46 of the ring to abut against inner surface 46 of the end hole 24. An interference fit forms between fastener head 34, ring 30, and plate 22 in which these elements fit together such that each element obstructs the movement of the other elements. Hoop stress of ring 30 on head 34 fixedly attaches fastener 32 to plate 22.

bc67 Ring 30 may be capable of swiveling within a hole 24 so that one portion of ring 30 is adjacent to the upper surface 26 of bone plate 22 while another portion of the ring lies adjacent to the lower surface 28 of the bone plate. In one embodiment, ring 30 may sufficiently thin to reside within end hole 24 without extending beyond the upper or lower surface 26, 28 of bone plate 22. The ring 30 and fastener head 34 remain within end hole 24 so that the spinal plating system 20 may have a minimal profile width. Having rings 30 and the fastener heads 34 which do not extend above the upper surface 26 or below the lower surface 28 of plate 22 may prevent the rings and heads from contacting adjacent tissue structures. In other embodiments, however, fasteners 32 may

be capable of being angulated relative to bone plate 22 such that the rings 30 extend from the end holes 24 beyond upper and/or lower surfaces of the bone plate.

In one embodiment, the spinal plating system 20 is prepared for surgical implantation by positioning rings 30 within end holes 24. During the surgical procedure, holes may be drilled and tapped into the bones to which plate 22 is to be attached. Plate 22 may then positioned adjacent to the bones and over the holes in the bone. Fasteners 32 may be placed through a ring 30 and into the bone holes. Each fastener 32 may be obliquely angulated into the plate 22. The fasteners 32 may be inserted into the bone until the fastener heads 34 expand the rings 30 against the inner surfaces 46 of the holes 24; thus fixing the fasteners to the rings, and the rings to the plate 22. If necessary, a fastener 42 may be positioned in one of the central holes 38.

In one embodiment, ring 30 has an outer width that is less than or about equal to the width of an end hole 24 in bone plate 22 at a location between an upper surface 26 and lower surface 28 of the bone plate. The width of each end hole 24 proximate the upper and lower surfaces 26, 28 of bone plate 22 is less than or about equal to an outer width of ring 30. The width of the ring may inhibit a ring positioned in a hole from falling out of the hole. Prior to surgery, a ring 30 may be positioned within each end hole 24 of bone plate 22. When seated within hole 24, ring 30 may be capable of swiveling within the hole, but the ring is inhibited from falling out of the hole because of reduced width of the hole proximate the upper and lower surfaces 26, 28 of the plate 22. A surgeon may use a bone plate 22 having rings 30 positioned within holes 24 prior to surgery. Alternatively, rings 30 may be manually positioned within holes 24 during surgery.

Texturing the outer surface 48 of a ring 30 or an inner surface 46 of a hole 24 may further inhibit movement of a fastener 32 with respect to a bone plate 22. Both surfaces may be textured to more effectively inhibit movement of a fastener 32 with respect to a bone plate 22. During manufacturing procedures, the outer surface 48 of ring 30 and the inner surface of end hole 24 are formed as relatively smooth surfaces. While the friction between these smooth surfaces tends to be sufficient to maintain fastener 32 in a fixed

position with respect to plate 22; under stressful conditions ring 30 may rotate within hole 24. By providing at least one textured surface, the coefficient of friction between hole 24 and ring 30 is increased. The increase in friction between hole 24 and ring 30 may help to inhibit fastener movement relative to plate 22.

5        Several types of textured surfaces may be used to increase the coefficient of friction between ring 30 and hole 24. In general, any process that transforms a relatively smooth surface into a textured surface having an increased coefficient of friction may be used. Methods for forming a textured surface include, but are not limited to: sanding, forming grooves within a surface, shot peening processes, electric discharge processes, and embedding of hard particles within a surface.

10        A shot peening process for forming a textured surface is described in U.S. Patent No. 5,526,664 to Vetter which is incorporated by reference as if set forth herein. In general, a shot peening process involves propelling a stream of hardened balls, typically made of steel, at a relatively high velocity at a surface. To create a pattern upon an area of the surface the stream is typically moved about the surface. The speed by which the stream is moved about the surface determines the type of textured surface formed.

15        An electrical discharge process is based on the principle of removal of portions of a metal surface by spark discharges. Typically a spark is generated between the surface to be treated and an electrode by creating potential differential between the tool and the electrode. The spark produced tends to remove a portion of the surface disposed between the electrode and the surface. Typically, the electrode is relatively small such that only small portions of the surface are removed. By moving the electrode about the surface numerous cavities may be formed within the surface. Typically these cavities are somewhat pyramidal in shape. Various patterns may be formed within the surface depending on how the electrode is positioned during the discharge. Electric discharge machines are well known in the art. A method for forming a frictional surface within a metal surface using an electric discharge process is described in U.S. Patent No. 20        4,964,641 to Miesch et al., which is incorporated by reference as if set forth herein.

Embedding hardened particles in a surface produces a textured surface. A method for embedding hardened particles in a metal surface is described in U.S. Patent No. 4,768,787 to Shira, which is incorporated by reference as if set forth herein. The method of Shira involves using a laser or other high-energy source to heat the surface such that the surface melts in selected areas. Just before the molten area re-solidifies, a stream of abrasive particles is directed to the area. In this manner some of the particles tend to become embedded within the molten surface. The particles typically have a number of sharp edges that protrude from the surface after the particles have been embedded within the surface.

19 hsc 17 Any of the above methods of texturing may be used in combination with another method. For example, the inner surface 46 of hole 24 may be textured using a pattern of grooves. The outer surface 48 of ring 30, however, may be textured using an electrical discharge method. When coupled together the textured surfaces of hole 24 and ring 30 may interact with each other to provide additional resistance to movement of the ring within the hole.

Figure 5 illustrates an embodiment of fastener 100. The fastener 100 may include fastener head 102, opening 104, optional grooves 106, holes 108, shank 110 and threads 112. Opening 104 accepts a drive tool, such as drive tool 114, which is described below. The opening 104, grooves 106 and holes 108 accept locking mechanism 116, as described below. Holes 108 extend from the outer surface 118 of head 102 to the opening 104. In one embodiment, the outer surface 118 is substantially cylindrical. In another embodiment, the head 102 tapers from a widest portion near the upper surface of the head to a narrowest portion near the shank 110.

Figure 6 is a side view of the head 102 of an embodiment of fastener 100 showing holes 108 and optional rim 120. Rim 120 may serve to limit the insertion of fastener 100 into a ring 30 during use.



Figure 7 is a top view of the head 102 of a fastener 100 with optional grooves 106. Figure 8 shows an alternate embodiment of fastener 100 having a hexagonal shape opening 104 and no grooves.

5 ~~Figure 9 illustrates a locking mechanism 116 used with fastener 100. Locking mechanism 116 includes top 122 with shafts 124 extending downwards and outwards from the top. Prongs 126 are located at ends of shafts 124. Prongs 126 may be substantially parallel to each other and also may be substantially parallel to the locking mechanism top 122. The shafts 124 have a spring-like action which allows the shafts 124 to be compressed. The spring-like action also allows the shafts to return to an original configuration when not compressed.~~

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000  
1005  
1010  
1015  
1020  
1025  
1030  
1035  
1040  
1045  
1050  
1055  
1060  
1065  
1070  
1075  
1080  
1085  
1090  
1095  
1100  
1105  
1110  
1115  
1120  
1125  
1130  
1135  
1140  
1145  
1150  
1155  
1160  
1165  
1170  
1175  
1180  
1185  
1190  
1195  
1200  
1205  
1210  
1215  
1220  
1225  
1230  
1235  
1240  
1245  
1250  
1255  
1260  
1265  
1270  
1275  
1280  
1285  
1290  
1295  
1300  
1305  
1310  
1315  
1320  
1325  
1330  
1335  
1340  
1345  
1350  
1355  
1360  
1365  
1370  
1375  
1380  
1385  
1390  
1395  
1400  
1405  
1410  
1415  
1420  
1425  
1430  
1435  
1440  
1445  
1450  
1455  
1460  
1465  
1470  
1475  
1480  
1485  
1490  
1495  
1500  
1505  
1510  
1515  
1520  
1525  
1530  
1535  
1540  
1545  
1550  
1555  
1560  
1565  
1570  
1575  
1580  
1585  
1590  
1595  
1600  
1605  
1610  
1615  
1620  
1625  
1630  
1635  
1640  
1645  
1650  
1655  
1660  
1665  
1670  
1675  
1680  
1685  
1690  
1695  
1700  
1705  
1710  
1715  
1720  
1725  
1730  
1735  
1740  
1745  
1750  
1755  
1760  
1765  
1770  
1775  
1780  
1785  
1790  
1795  
1800  
1805  
1810  
1815  
1820  
1825  
1830  
1835  
1840  
1845  
1850  
1855  
1860  
1865  
1870  
1875  
1880  
1885  
1890  
1895  
1900  
1905  
1910  
1915  
1920  
1925  
1930  
1935  
1940  
1945  
1950  
1955  
1960  
1965  
1970  
1975  
1980  
1985  
1990  
1995  
2000  
2005  
2010  
2015  
2020  
2025  
2030  
2035  
2040  
2045  
2050  
2055  
2060  
2065  
2070  
2075  
2080  
2085  
2090  
2095  
2100  
2105  
2110  
2115  
2120  
2125  
2130  
2135  
2140  
2145  
2150  
2155  
2160  
2165  
2170  
2175  
2180  
2185  
2190  
2195  
2200  
2205  
2210  
2215  
2220  
2225  
2230  
2235  
2240  
2245  
2250  
2255  
2260  
2265  
2270  
2275  
2280  
2285  
2290  
2295  
2300  
2305  
2310  
2315  
2320  
2325  
2330  
2335  
2340  
2345  
2350  
2355  
2360  
2365  
2370  
2375  
2380  
2385  
2390  
2395  
2400  
2405  
2410  
2415  
2420  
2425  
2430  
2435  
2440  
2445  
2450  
2455  
2460  
2465  
2470  
2475  
2480  
2485  
2490  
2495  
2500  
2505  
2510  
2515  
2520  
2525  
2530  
2535  
2540  
2545  
2550  
2555  
2560  
2565  
2570  
2575  
2580  
2585  
2590  
2595  
2600  
2605  
2610  
2615  
2620  
2625  
2630  
2635  
2640  
2645  
2650  
2655  
2660  
2665  
2670  
2675  
2680  
2685  
2690  
2695  
2700  
2705  
2710  
2715  
2720  
2725  
2730  
2735  
2740  
2745  
2750  
2755  
2760  
2765  
2770  
2775  
2780  
2785  
2790  
2795  
2800  
2805  
2810  
2815  
2820  
2825  
2830  
2835  
2840  
2845  
2850  
2855  
2860  
2865  
2870  
2875  
2880  
2885  
2890  
2895  
2900  
2905  
2910  
2915  
2920  
2925  
2930  
2935  
2940  
2945  
2950  
2955  
2960  
2965  
2970  
2975  
2980  
2985  
2990  
2995  
3000  
3005  
3010  
3015  
3020  
3025  
3030  
3035  
3040  
3045  
3050  
3055  
3060  
3065  
3070  
3075  
3080  
3085  
3090  
3095  
3100  
3105  
3110  
3115  
3120  
3125  
3130  
3135  
3140  
3145  
3150  
3155  
3160  
3165  
3170  
3175  
3180  
3185  
3190  
3195  
3200  
3205  
3210  
3215  
3220  
3225  
3230  
3235  
3240  
3245  
3250  
3255  
3260  
3265  
3270  
3275  
3280  
3285  
3290  
3295  
3300  
3305  
3310  
3315  
3320  
3325  
3330  
3335  
3340  
3345  
3350  
3355  
3360  
3365  
3370  
3375  
3380  
3385  
3390  
3395  
3400  
3405  
3410  
3415  
3420  
3425  
3430  
3435  
3440  
3445  
3450  
3455  
3460  
3465  
3470  
3475  
3480  
3485  
3490  
3495  
3500  
3505  
3510  
3515  
3520  
3525  
3530  
3535  
3540  
3545  
3550  
3555  
3560  
3565  
3570  
3575  
3580  
3585  
3590  
3595  
3600  
3605  
3610  
3615  
3620  
3625  
3630  
3635  
3640  
3645  
3650  
3655  
3660  
3665  
3670  
3675  
3680  
3685  
3690  
3695  
3700  
3705  
3710  
3715  
3720  
3725  
3730  
3735  
3740  
3745  
3750  
3755  
3760  
3765  
3770  
3775  
3780  
3785  
3790  
3795  
3800  
3805  
3810  
3815  
3820  
3825  
3830  
3835  
3840  
3845  
3850  
3855  
3860  
3865  
3870  
3875  
3880  
3885  
3890  
3895  
3900  
3905  
3910  
3915  
3920  
3925  
3930  
3935  
3940  
3945  
3950  
3955  
3960  
3965  
3970  
3975  
3980  
3985  
3990  
3995  
4000  
4005  
4010  
4015  
4020  
4025  
4030  
4035  
4040  
4045  
4050  
4055  
4060  
4065  
4070  
4075  
4080  
4085  
4090  
4095  
4100  
4105  
4110  
4115  
4120  
4125  
4130  
4135  
4140  
4145  
4150  
4155  
4160  
4165  
4170  
4175  
4180  
4185  
4190  
4195  
4200  
4205  
4210  
4215  
4220  
4225  
4230  
4235  
4240  
4245  
4250  
4255  
4260  
4265  
4270  
4275  
4280  
4285  
4290  
4295  
4300  
4305  
4310  
4315  
4320  
4325  
4330  
4335  
4340  
4345  
4350  
4355  
4360  
4365  
4370  
4375  
4380  
4385  
4390  
4395  
4400  
4405  
4410  
4415  
4420  
4425  
4430  
4435  
4440  
4445  
4450  
4455  
4460  
4465  
4470  
4475  
4480  
4485  
4490  
4495  
4500  
4505  
4510  
4515  
4520  
4525  
4530  
4535  
4540  
4545  
4550  
4555  
4560  
4565  
4570  
4575  
4580  
4585  
4590  
4595  
4600  
4605  
4610  
4615  
4620  
4625  
4630  
4635  
4640  
4645  
4650  
4655  
4660  
4665  
4670  
4675  
4680  
4685  
4690  
4695  
4700  
4705  
4710  
4715  
4720  
4725  
4730  
4735  
4740  
4745  
4750  
4755  
4760  
4765  
4770  
4775  
4780  
4785  
4790  
4795  
4800  
4805  
4810  
4815  
4820  
4825  
4830  
4835  
4840  
4845  
4850  
4855  
4860  
4865  
4870  
4875  
4880  
4885  
4890  
4895  
4900  
4905  
4910  
4915  
4920  
4925  
4930  
4935  
4940  
4945  
4950  
4955  
4960  
4965  
4970  
4975  
4980  
4985  
4990  
4995  
5000  
5005  
5010  
5015  
5020  
5025  
5030  
5035  
5040  
5045  
5050  
5055  
5060  
5065  
5070  
5075  
5080  
5085  
5090  
5095  
5100  
5105  
5110  
5115  
5120  
5125  
5130  
5135  
5140  
5145  
5150  
5155  
5160  
5165  
5170  
5175  
5180  
5185  
5190  
5195  
5200  
5205  
5210  
5215  
5220  
5225  
5230  
5235  
5240  
5245  
5250  
5255  
5260  
5265  
5270  
5275  
5280  
5285  
5290  
5295  
5300  
5305  
5310  
5315  
5320  
5325  
5330  
5335  
5340  
5345  
5350  
5355  
5360  
5365  
5370  
5375  
5380  
5385  
5390  
5395  
5400  
5405  
5410  
5415  
5420  
5425  
5430  
5435  
5440  
5445  
5450  
5455  
5460  
5465  
5470  
5475  
5480  
5485  
5490  
5495  
5500  
5505  
5510  
5515  
5520  
5525  
5530  
5535  
5540  
5545  
5550  
5555  
5560  
5565  
5570  
5575  
5580  
5585  
5590  
5595  
5600  
5605  
5610  
5615  
5620  
5625  
5630  
5635  
5640  
5645  
5650  
5655  
5660  
5665  
5670  
5675  
5680  
5685  
5690  
5695  
5700  
5705  
5710  
5715  
5720  
5725  
5730  
5735  
5740  
5745  
5750  
5755  
5760  
5765  
5770  
5775  
5780  
5785  
5790  
5795  
5800  
5805  
5810  
5815  
5820  
5825  
5830  
5835  
5840  
5845  
5850  
5855  
5860  
5865  
5870  
5875  
5880  
5885  
5890  
5895  
5900  
5905  
5910  
5915  
5920  
5925  
5930  
5935  
5940  
5945  
5950  
5955  
5960  
5965  
5970  
5975  
5980  
5985  
5990  
5995  
6000  
6005  
6010  
6015  
6020  
6025  
6030  
6035  
6040  
6045  
6050  
6055  
6060  
6065  
6070  
6075  
6080  
6085  
6090  
6095  
6100  
6105  
6110  
6115  
6120  
6125  
6130  
6135  
6140  
6145  
6150  
6155  
6160  
6165  
6170  
6175  
6180  
6185  
6190  
6195  
6200  
6205  
6210  
6215  
6220  
6225  
6230  
6235  
6240  
6245  
6250  
6255  
6260  
6265  
6270  
6275  
6280  
6285  
6290  
6295  
6300  
6305  
6310  
6315  
6320  
6325  
6330  
6335  
6340  
6345  
6350  
6355  
6360  
6365  
6370  
6375  
6380  
6385  
6390  
6395  
6400  
6405  
6410  
6415  
6420  
6425  
6430  
6435  
6440  
6445  
6450  
6455  
6460  
6465  
6470  
6475  
6480  
6485  
6490  
6495  
6500  
6505  
6510  
6515  
6520  
6525  
6530  
6535  
6540  
6545  
6550  
6555  
6560  
6565  
6570  
6575  
6580  
6585  
6590  
6595  
6600  
6605  
6610  
6615  
6620  
6625  
6630  
6635  
6640  
6645  
6650  
6655  
6660  
6665  
6670  
6675  
6680  
6685  
6690  
6695  
6700  
6705  
6710  
6715  
6720  
6725  
6730  
6735  
6740  
6745  
6750  
6755  
6760  
6765  
6770  
6775  
6780  
6785  
6790  
6795  
6800  
6805  
6810  
6815  
6820  
6825  
6830  
6835  
6840  
6845  
6850  
6855  
6860  
6865  
6870  
6875  
6880  
6885  
6890  
6895  
6900  
6905  
6910  
6915  
6920  
6925  
6930  
6935  
6940  
6945  
6950  
6955  
6960  
6965  
6970  
6975  
6980  
6985  
6990  
6995  
7000  
7005  
7010  
7015  
7020  
7025  
7030  
7035  
7040  
7045  
7050  
7055  
7060  
7065  
7070  
7075  
7080  
7085  
7090  
7095  
7100  
7105  
7110  
7115  
7120  
7125  
7130  
7135  
7140  
7145  
7150  
7155  
7160  
7165  
7170  
7175  
7180  
7185  
7190  
7195  
7200  
7205  
7210  
7215  
7220  
7225  
7230  
7235  
7240  
7245  
7250  
7255  
7260  
7265  
7270  
7275  
7280  
7285  
7290  
7295  
7300  
7305  
7310  
7315  
7320  
7325  
7330  
7335  
7340  
7345  
7350  
7355  
7360  
7365  
7370  
7375  
7380  
7385  
7390  
7395  
7400  
7405  
7410  
7415  
7420  
7425  
7430  
7435  
7440  
7445  
7450  
7455  
7460  
7465  
7470  
7475  
7480  
7485  
7490  
7495  
7500  
7505  
7510  
7515  
7520  
7525  
7530  
7535  
7540  
7545  
7550  
7555  
7560  
7565  
7570  
7575  
7580  
7585  
7590  
7595  
7600  
7605  
7610  
7615  
7620  
7625  
7630  
7635  
7640  
7645  
7650  
7655  
7660  
7665  
7670  
7675  
7680  
7685  
7690  
7695  
7700  
7705  
7710  
7715  
7720  
7725  
7730  
7735  
7740  
7745  
7750  
7755  
7760  
7765  
7770  
7775  
7780  
7785  
7790  
7795  
7800  
7805  
7810  
7815  
7820  
7825  
7830  
7835  
7840  
7845  
7850  
7855  
7860  
7865  
7870  
7875  
7880  
7885  
7890  
7895  
7900  
7905  
7910  
7915  
7920  
7925  
7930  
7935  
7940  
7945  
7950  
7955  
7960  
7965  
7970  
7975  
7980  
7985  
7990  
7995  
8000  
8005  
8010  
8015  
8020  
8025  
8030  
8035  
8040  
8045  
8050  
8055  
8060  
8065  
8070  
8075  
8080  
8085  
8090  
8095  
8100  
8105  
8110  
8115  
8120  
8125  
8130  
8135  
8140  
8145  
8150  
8155  
8160  
8165  
8170  
8175  
8180  
8185  
8190  
8195  
8200  
8205  
8210  
8215  
8220  
8225  
8230  
8235  
8240  
8245  
8250  
8255  
8260  
8265  
8270  
8275  
8280  
8285  
8290  
8295  
8300  
8305  
8310  
8315  
8320  
8325  
8330  
8335  
8340  
8345  
8350  
8355  
8360  
8365  
8370  
8375  
8380  
8385  
8390  
8395  
8400  
8405  
8410  
8415  
8420  
8425  
8430  
8435  
8440  
8445  
8450  
8455  
8460  
8465  
8470  
8475  
8480  
8485  
8490  
8495  
8500  
8505  
8510  
8515  
8520  
8525  
8530  
8535  
8540  
8545  
8550  
8555  
8560  
8565  
8570  
8575  
8580  
8585  
8590  
8595  
8600  
8605  
8610  
8615  
8620  
8625  
8630  
8635  
8640  
8645  
8650  
8655  
8660  
8665  
8670  
8675  
8680  
8685  
8690  
8695  
8700  
8705  
8710  
8715  
8720  
8725  
8730  
8735  
8740  
8745  
8750  
8755  
8760  
8765  
8770  
8775  
8780  
8785  
8790  
8795  
8800  
8805  
8810  
8815  
8820  
8825  
8830  
8835  
8840  
8845  
8850  
8855  
8860  
8865  
8870  
8875  
8880  
8885  
8890  
8895  
8900  
8905  
8910  
8915  
8920  
8925  
8930  
8935  
8940  
8945  
8950  
8955  
8960  
8965  
8970  
8975  
8980  
8985  
8990  
8995  
9000  
9005  
9010  
9015  
9020  
9025  
9030  
9035  
9040  
9045  
9050  
9055  
9060  
9065  
9070  
9075  
9080  
9085  
9090  
9095  
9100  
9105  
9110  
9115  
9120  
9125  
9130  
9135  
9140  
9145  
9150  
9155  
9160  
9165  
9170  
9175  
9180  
9185  
9190  
9195  
9200  
9205  
9210  
9215  
9220  
9225  
9230  
9235  
9240  
9245  
9250  
9255  
9260  
9265  
9270  
9275  
9280  
9285  
9290  
9295  
9300  
9305  
9310  
9315  
9320  
9325  
9330  
9335  
9340  
9345  
9350  
9355  
9360  
9365  
9370  
9375  
9380  
9385  
9390  
9395  
9400  
9405  
9410  
9415  
9420  
9425  
9430  
9435  
9440  
9445  
9450  
9455  
9460  
9465  
9470  
9475  
9480  
9485  
9490  
9495  
9500  
9505  
9510  
9515  
9520  
9525  
9530  
9535  
9540  
9545  
9550  
9555  
9560  
9565  
9570  
9575  
9580  
9585  
9590  
9595  
9600  
9605  
9610  
9615  
9620  
9625  
9630  
9635  
9640  
9645  
9650  
9655  
9660  
9665  
9670  
9675  
9680  
9685  
9690  
9695  
9700  
9705  
9710  
9715  
9720  
9725  
9730  
9735  
9740  
9745  
9750  
9755  
9760  
9765  
9770  
9775  
9780  
9785  
9790  
9795  
9800  
9805  
9810  
9815  
9820  
9825  
9830  
9835  
9840  
9845  
9850  
9855  
9860  
9865  
9870  
9875  
9880  
9885  
9890  
9895  
9900  
9905  
9910  
9915  
9920  
9925  
9930  
9935  
9940  
9945  
9950  
9955  
9960  
9965  
9970  
9975  
9980  
9985  
9990  
9995  
10000  
10005  
10010  
10015  
10020  
10025  
10030  
10035  
10040  
10045  
10050  
10055  
10060  
10065  
10070  
10075  
10080  
10085  
10090  
10095  
10100  
10105  
10110  
10115  
10120  
10125  
10130  
10135  
10140  
10145  
10150  
10155  
10160  
10165  
10170  
10175  
10180  
10185  
10190  
10195  
10200  
10205  
10210  
10215  
10220

the cavity may slide over and compress the shafts 124 and prongs 126 of a locking mechanism 116.

Figure 12a shows a bottom view of an embodiment of a driver head 176 of an insertion/extraction tool 114. The driver head of Figure 12a may be used with the type of fastener head 102 shown in Figure 7. The driver head 176 has cavity 178 which allows the driver head to slide over and compress a locking mechanism 116. The driver head 176 includes ridges 180 for engaging complementary grooves 106 in the opening 104 of a fastener head 102. Figure 12b shows an alternate embodiment of a driver head 176 of an insertion/extraction tool 114. The driver head of Figure 12b may be used with the type of fastener head 102 shown in Figure 8. The driver head 176 has cavity 178 which allows the driver head to slide over and compresses a locking mechanism 116. The driver head 176 may be hexagonal shaped to mate with opening 104 of a fastener head 102.

Figure 13 shows a cross sectional view of an embodiment of a fastener 100, locking mechanism 116, and insertion/extraction tool 114 during the insertion process. Driver head 176 inserts into opening 104 of fastener head 102. Shafts 124 of locking mechanism 116 are compressed within cavity 178 of driver head 176. The compression of shafts 124 causes prongs 126 to retract in holes 108, which allow fastener head 102 to be inserted into a ring 130 without interference by extended prongs 126. When insertion/extraction tool 114 is removed, the shafts 124 uncompress, which causes the prongs 126 to extend out of holes 108.

Figure 14 shows a cross sectional view of an embodiment of a fastener 100, locking mechanism 116, and ring 130 after the fastener has been fully inserted in the ring and the insertion/extraction tool 114 has been removed. Shafts 124 of locking mechanism 116 are uncompressed, allowing prongs 126 to extend out of holes 108 in fastener head 102. Prongs 126 extend into groove 132 on the ring 130.

To remove a threaded fastener 100 from ring 130, insertion/extraction tool 114 is inserted in the opening 104 in fastener head 102 to compress the shafts 124 of the locking mechanism 116. Compressing the shafts 124 causes the prongs 126 to retract through

holes 108 and removes the connection between the prongs and the ring 130. The tool 114 may then be rotated to remove the fastener 100 from the bone.

6 C97 After insertion of a fastener 100 and locking mechanism 116 into a bone, if the fastener 100 becomes loose within the bone, fastener backout from the bone plate may be resisted by the locking mechanism-groove connection between locking mechanism 116 and the ring 130. Thus, even if fastener shank 110 loosens within the bone, the fastener head 102 will tend to remain within ring 130 in the hole 24 of the plate 22. There may be some freedom of movement in the connection between the prongs 126 and the groove 130 to allow a fastener 100 to back out slightly from a bone after insertion.

During the surgical procedure for attaching a bone plate to bones using the devices depicted in Figures 5-14, holes may be drilled and tapped into the bones to which the bone plate 22 is to be attached. The bone plate 22 may be positioned adjacent to the bones. Rings 130 may be positioned within each end hole 24 before or during the surgical procedure. A fastener 100, with a pre-inserted locking mechanism, may be positioned through a ring 130. An insertion/extraction tool 114 may be inserted in the opening 104 of threaded fastener 100 to compress the locking mechanism 116 within the cavity of the driver head of the tool. Compressing the locking mechanism 116 retracts the prongs 126 of the locking mechanism within the fastener opening 104. The fastener 100 may then be rotated to insert the fastener 100 into a bone. As the fastener 100 is rotated, fastener head 102 moves into the ring 130. Movement of head 102 into ring 130 causes the ring to expand against the end hole 24 to fix the fastener 100 relative to the plate 22. Once the fastener 100 is fully inserted, insertion/extraction tool 114 is removed. Removing the tool 114 causes the locking mechanism 116 to uncompress so that the prongs 126 extend through the holes 108 in the fastener head 102 and engage ring the groove 132 in the ring 130. Fasteners 100 may be inserted through the remaining end holes 24 and into bone to securely attach the plate 22 to the bones.

Figure 15 illustrates an embodiment of a fastener 200 with fastener head 202 having groove 204. When a fastener 200 is inserted through a ring 230 positioned in a plate 22, the groove 204 may engage fingers 232 on ring 230 (the ring shown in Figures

19 and 20) to secure the fastener 200 within the ring 230. Fastener 200 may include the head 202 and shank 206 with threading 208. Head 202 may include opening 210 configured to accept a driving tool.

The engagement of a finger 232 of a ring 230 on groove 204 may inhibit fastener 200 from backing out of the ring after insertion of the fastener into the plate 22. In an embodiment, the outer surface of head 202 is substantially cylindrical. In another embodiment, as shown in Figure 16, the head 202 may taper. The widest portion of the head 202 may be near the top surface of the head, and the narrowest portion may be near the shank 206.

Figure 17 illustrates an embodiment of a fastener 200 which has radial slots 212 extending from the outer surface of the head into the opening 210. The radial slots 212 may allow a portion of head 202 to contract during insertion. The radial slots 212 may also be used to engage a portion of a drive head of an insertion/extraction tool (not shown).

Figures 15, 16, and 17 illustrate fastener heads 202 wherein the grooves 204 are rims along top edges of the heads. Figure 18 illustrates an embodiment of a fastener 200 wherein the groove 204 is located at a position along the side of the fastener head 202. The groove 204 may be located at any position along the side of the fastener head 202. When the fastener head 202 is driven through a ring 230, the interaction of the fastener head, the ring, and the end hole 24 allows fingers 232 of the ring to snap into the groove 214. The fingers 232 may secure the fastener head 202 to the ring 230.

Figures 19 and 20 show perspective views of embodiments of ring 230 that may be used with fasteners having a groove. Ring 230 may include bottom 234, top 238, an outer surface 48, an inner surface 60, gap 36, and slots 240 and notches 242. The slots 240 and notches 240 may form the fingers 232. Gap 36 may allow ring 230 to contract. Contraction of the ring 230 may facilitate the insertion of the ring into an end hole 24 in a bone plate 22. Gap 36 may also allow the ring 230 to expand against the end hole 24 when a fastener head 202 passes into the ring. Expansion of the ring against the hole 24 fixes the fastener 200 relative to the bone plate 22.

1  
2  
3  
4  
5 In some embodiments, outer surface 48 of the ring 230 may be textured to increase the coefficient of friction between ring 230 and the hole 24. In some embodiments, inner surface 60 of the ring 230 may be tapered to match a tapered head of a fastener 200. Having tapered surfaces may facilitate the expansion of ring in an end hole 24 during insertion of the fastener into the bone plate system 20.

6  
7  
8  
9  
10 The shape of the end hole 24 may push the fingers 232 inwards past the edge of the groove 204 of a fastener 200 when the groove is inserted into a ring 230 so that the groove passes an upper edge of the ring slots 240. The inward positioned fingers 232 may inhibit fastener 200 from backing out of the ring 230 and the hole 24. When the fastener 200 is inserted into the ring 230, the fastener head 202 may expand the outside surface 48 of the ring against the inner surface 46 of the end hole 24 to fix the fastener 200 to the ring 230, and the ring to the plate 22.

11  
12  
13  
14  
15 Figure 21 is a perspective view of an embodiment of a ring that may be used with fasteners 200 that have rims 204, such as the fasteners shown in Figure 15-17. Ring 430 may include bottom 432, top 434, outer surface 48, inner surface 60, gap 36, notches 436, and ridges 438. Notches 436 divide the ring 430 into segments or paddles 440. Notches 436 and gap 36 may allow ring 430 to contract, facilitating the insertion of the ring into a hole 24 of a bone plate 22. Notches 436 and gap 36 may also allow ring 430 to expand when a fastener head 202 passes into the ring to fix the position of the fastener relative to the bone plate 22. Notches 436 may also allow paddles 436 to bend outwards during insertion of a fastener 200. The outer surface 48 and/or the inner surface 60 may be textured. The inner surface of the ring 430 may be tapered to correspond to the taper of a fastener head 202.

16  
17  
18  
19  
20  
21  
22  
23  
24  
25 Figure 22 illustrates an embodiment of an insertion tool/extraction tool 450 for use with a fastener 200 and ring 430. Insertion/extraction tool 450 may include shaft 452, handle 454, driver head 456, and extraction member 458. At one end of shaft 452 is handle 454 for turning the tool during insertion and removal of a fastener 200. The illustration shows a T-handle, but any other type of handle that allows sufficient torque to be applied to the fastener 200 to allow for insertion or removal of the fastener may be

used. At the opposite end of shaft 452 from handle 454 is driver head 456. The outer surface of driver head 456 may be shaped complementary to the shape of the opening 210 in the head 202 of the fastener 200.

The extraction member 458 shown in Figure 22 may include grip 459, passage 460, (shown in Figure 23c), tip 462, and extraction head 464. The passage 460 extends through the grip 459 and the extraction head 464. During the insertion process, extraction member 458 may be removed from shaft 452. To extract a fastener from a ring 430, extraction member 458 may be slid back on to shaft 452. Driver head 456 is inserted into the opening 210 of the fastener 200. Extraction member 458 slides down shaft 452 until tip 462 of extraction head 464 contacts the top of the ring 430. Downwards pressure on the extraction member 458 forces paddles 440 of the ring 430 outwards, and disengages the ridge 438 on the paddles 440 from the rim 204 on the fastener head 202. The fastener 200 may then be backed out of the plate 22 by rotating the shaft 452 with the handle 454. Preferably, rotating shaft 452 does not rotate the extraction member 458.

Figure 23a, 23b, and 23c show partial cross sectional views of a threaded fastener 200, ring 430, and insertion/extraction tool 450 during the insertion and extraction processes. Referring to Figure 23a, driver head 456 of insertion/extraction tool 450 is inserted in opening 210 of fastener head 202. Ring 430 is positioned inside a hole 24 in a bone plate and the bone plate is positioned on a bone (bone and bone plate not shown). Fastener 200 is screwed into the bone until the outer surface of fastener head 202 contacts the surfaces of the paddles 440. The tapering of the outer surface of fastener head 202 provides a ramping force on the surfaces of the paddles 440, to bend the paddles outwards as fastener 200 is screwed farther into the bone.

In Figure 23b, fastener 200 has been screwed in to the desired depth. Fastener head 202 penetrates ring 430 far enough to allow ridges 438 to snap onto rim 204 on fastener head 202. Driver head 456 of insertion/extraction tool 450 is shown still inserted in opening 210 prior to removal from the opening. After insertion, if the fastener 200 becomes loose within the bone, fastener backout from the bone plate may be resisted by the ridge-rim connection between fastener head 202 and ring 430. Thus, even if the

fastener shank loosens within the bone, the fastener head 202 will tend to remain within ring 430 in the hole 24 of the plate 22 so as not to protrude from the plate into surrounding body tissue. In some embodiments, there may be some freedom of movement in the connection between the ridges 438 on the paddles 440 and the rim 204 to allow a fastener 200 to back out slightly from a bone after insertion. Typically, the freedom of movement is limited so that the fastener head 202 may not protrude from the plate 22.

Figure 23c shows insertion/extraction tool 250 being used to remove a fastener 200. Driver head 256 is inserted in opening 210 of fastener 200. Extraction head 464 is slid down shaft 452 of insertion/extraction tool 450 until the sloped surface of tip 462 applies a wedging force against the sloped upper surfaces of paddles 440. The wedging force bends the paddles 440 outwards to disengage the ridges 438 from the rim 204. Fastener 200 may then be backed out of the bone, the ring 430 and the plate 22.

The plate, fasteners, and locking mechanisms may be made of steel (e.g., stainless steel), titanium, steel alloys or titanium alloys. These materials are generally nontoxic, bio-compatible, strong, and non-corrosive. Other materials that have these properties may also be used. The plate and the rings may be made of a number of bio-compatible materials including metals, plastics, and composites.

Any of the embodiments described above may be used individually or in combination with other embodiments described above. Further modifications and alternative embodiments of various aspects of the invention will be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the general manner of carrying out the invention. It is to be understood that the forms of the invention shown and described herein are to be taken as examples of embodiments. Elements and materials may be substituted for those illustrated and described herein, parts and processes may be reversed, and certain features of the invention may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of

this description of the invention. Changes may be made in the elements described herein without departing from the spirit and scope of the invention as described in the following claims.

10045206-11904  
FOFF-9025FO01